



## BEARING-SINGAPORE (PTE)LTD.



40 mm x 62 mm x 12 mm NSK 6908DDU deep groove ball bearings

Bearing No. 6908DDU

6908DDU Bearing 2D drawings and 3D CAD models

Size	40x62x12 mm
Bore Diameter	40 mm
Outer Diameter	62 mm
Width	12 mm
d	40 mm
D	62 mm
B	12 mm
C	12 mm
r min.	0,6 mm
da min.	44 mm
da max	46 mm
Da max.	58 mm
ra max.	0,6 mm
Weight	0,112 Kg
Basic dynamic load rating (C)	13,7 kN
Basic static load rating (C0)	10 kN
(Grease) Lubrication Speed	6 300 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.11
EAN	0029176066719
Product Group	B00308
Enclosure	2 Seals



## BEARING-SINGAPORE (PTE)LTD.

Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	40MM Bore; 62MM Outside Diameter; 12MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Weight / LBS	1.575
Outside Diameter	2.441 Inch   62 Millimeter
Bore	1.575 Inch   40 Millimeter
Outer Race Width	0.472 Inch   12 Millimeter
bore diameter:	40 mm
closure type:	Double Sealed
outside diameter:	62 mm
internal clearance:	Normal Clearance
overall width:	12 mm
manufacturer upc number:	029176066719
bore type:	Round



## BEARING-SINGAPORE (PTE)LTD.

SRI	3.41
hidYobi	6908DDU
LangID	1
D_	62
SREX	0.04
B_	12
da min	44
hidTable	ecat_NSRDGB
SRE	3.58
mass	0.112
GRS rpm	6300
ra	0.6
SRIX	0.02
D_a	58
SRIN	0
C0	10
fo	15.7
SREN	0
DE_	58.747
Prod_Type3	DGBB_SR_DD
DA_	6.747
bomp	0
Z_	14
yobi	6908DDU
C_conv	13700
ALPHA_	0
SDM_	52
r	0.6
KBRG	6161
SBRG	19
DI_	45.253